

DR30H

CFM	Static Pressure in Inches W.G.											
	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.125	1.250	1.375
	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
400				932 4.9 / 0.05	1036 6.0 / 0.06	1130 6.9 / 0.08	1220 7.9 / 0.11	1303 8.9 / 0.13	1379 9.9 / 0.15	1455 10.9 / 0.18	1527 12.0 / 0.21	1594 13.0 / 0.23
500			894 4.5 / 0.04	1006 5.7 / 0.06	1104 6.7 / 0.08	1193 7.6 / 0.10	1276 8.5 / 0.12	1355 9.5 / 0.14	1429 10.5 / 0.17	1497 11.5 / 0.19	1567 12.6 / 0.22	1634 13.6 / 0.25
600		855 4.0 / 0.04	980 5.4 / 0.05	1085 6.5 / 0.07	1179 7.4 / 0.10	1263 8.4 / 0.12	1342 9.4 / 0.14	1418 10.4 / 0.17	1489 11.4 / 0.19	1554 12.4 / 0.22	1617 13.4 / 0.25	1681 14.4 / 0.28
700		951 5.1 / 0.05	1070 6.3 / 0.07	1171 7.3 / 0.09	1259 8.3 / 0.12	1341 9.3 / 0.14	1417 10.4 / 0.17	1486 11.4 / 0.19	1556 12.4 / 0.22	1620 13.4 / 0.25	1683 14.4 / 0.28	1741 15.4 / 0.31
800	926 4.8 / 0.05	1051 6.1 / 0.07	1163 7.3 / 0.09	1258 8.3 / 0.12	1345 9.4 / 0.14	1423 10.5 / 0.17	1495 11.5 / 0.19	1566 12.6 / 0.22	1629 13.5 / 0.25	1691 14.5 / 0.28	1751 15.6 / 0.31	
900	1042 6.0 / 0.07	1154 7.2 / 0.09	1257 8.3 / 0.12	1349 9.4 / 0.14	1431 10.6 / 0.17	1508 11.7 / 0.20	1579 12.8 / 0.23	1645 13.8 / 0.26	1708 14.8 / 0.29	1768 15.9 / 0.32		
1000	1157 7.2 / 0.09	1259 8.3 / 0.12	1355 9.5 / 0.14	1443 10.7 / 0.17	1522 11.9 / 0.20	1595 13.0 / 0.24	1664 14.1 / 0.27	1727 15.2 / 0.30	1789 16.2 / 0.33			
1100	1273 8.5 / 0.12	1366 9.7 / 0.15	1455 10.9 / 0.18	1538 12.2 / 0.21	1615 13.3 / 0.24	1685 14.4 / 0.28	1752 15.6 / 0.31					
1200	1389 10.0 / 0.16	1474 11.2 / 0.19	1556 12.4 / 0.22	1635 13.6 / 0.25	1709 14.8 / 0.29	1778 16.0 / 0.33						
1300	1505 11.6 / 0.20	1583 12.8 / 0.23	1660 14.0 / 0.27	1736 15.3 / 0.30								
1400	1618 13.4 / 0.25	1693 14.6 / 0.28	1765 15.8 / 0.32									

Max Sizeable RPM = 2000 RPM. Table shown extended beyond this point for reference only.

Motor BMN48-250I1-60-115 has an rpm range of 825 to 1800.

Motor BMN48-250I2-60-230/277 has an rpm range of 825 to 1800.

Motor CK48HF24KF01-50-115 has an rpm range of 825 to 1440.

Motor CK48HF24KF01-50-230 has an rpm range of 825 to 1440.

Motor CK48HF24KF01-60-115 has an rpm range of 825 to 1625.

Motor CK48HF24KF01-60-230 has an rpm range of 825 to 1700.

FloAire certifies that the DR30H shown herein is licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and 311 and complies with the requirements of the AMCA Certified Ratings Program. Tested to AMCA Standards 210 and 300. Meets California Energy Commission (CEC) Title 20 Regulations.

Performance shown is certified for Installation Type A: Free inlet, Free outlet. Speed shown is nominal. Performance is based on actual speed of test. Performance ratings do not include the effects of appurtenances (accessories).

Catalog #110F
May 2024



