

DU200H

CFM	Static Pressure in Inches W.G.											
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750
	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
1400			628 6.0 / 0.26	751 9.1 / 0.42	860 11.2 / 0.59	960 13.6 / 0.77	1050 15.4 / 0.97	1134 17.1 / 1.17	1210 19.7 / 1.38	1282 22 / 1.59	1350 25 / 1.82	1416 28 / 2.05
1900			679 7.8 / 0.35	784 9.7 / 0.53	882 11.7 / 0.72	973 14.0 / 0.94	1059 15.6 / 1.16	1140 17.3 / 1.39	1216 19.8 / 1.63	1288 23 / 1.88	1356 25 / 2.14	1422 28 / 2.41
2400		649 8.0 / 0.31	749 10.5 / 0.48	840 10.8 / 0.67	926 12.8 / 0.89	1008 14.7 / 1.12	1085 16.1 / 1.36	1159 17.9 / 1.62	1231 20 / 1.89	1299 23 / 2.17	1365 26 / 2.46	1429 29 / 2.76
2900	648 8.8 / 0.29	743 11.3 / 0.46	830 11.9 / 0.65	911 13.8 / 0.87	987 15.2 / 1.10	1060 16.2 / 1.34	1130 17.4 / 1.61	1197 19.3 / 1.89	1263 22 / 2.17	1326 24 / 2.48	1388 27 / 2.79	1447 30 / 3.11
3400	759 12.4 / 0.46	841 13.2 / 0.67	919 15.1 / 0.88	991 16.6 / 1.12	1060 17.3 / 1.36	1126 18.4 / 1.63	1189 20 / 1.91	1250 22 / 2.20	1310 24 / 2.51	1368 26 / 2.83	1425 29 / 3.16	1481 32 / 3.51
3900	871 14.9 / 0.69	943 17.3 / 0.93	1012 18.3 / 1.17	1078 18.9 / 1.43	1140 20 / 1.70	1200 22 / 1.98	1258 24 / 2.28	1315 26 / 2.59	1370 28 / 2.92	1423 30 / 3.26	1476 32 / 3.60	1527 34 / 3.96
4400	983 20 / 1.00	1047 20 / 1.26	1109 21 / 1.53	1168 22 / 1.81	1226 24 / 2.10	1281 26 / 2.41	1335 28 / 2.73	1387 30 / 3.06	1438 32 / 3.40	1488 34 / 3.76	1536 36 / 4.12	1584 37 / 4.50
4900	1094 23 / 1.38	1152 24 / 1.67	1208 26 / 1.97	1263 28 / 2.27	1316 29 / 2.59	1367 31 / 2.92	1417 33 / 3.26	1466 35 / 3.61	1513 37 / 3.97	1560 38 / 4.34		
5400	1206 28 / 1.84	1258 30 / 2.16	1310 32 / 2.49	1360 33 / 2.83	1409 35 / 3.17	1457 37 / 3.52	1503 39 / 3.88	1549 40 / 4.25	1593 41 / 4.63			
5900	1317 34 / 2.40	1365 36 / 2.75	1413 38 / 3.11	1459 40 / 3.47	1505 42 / 3.84	1549 43 / 4.22	1593 43 / 4.60					
6400	1429 42 / 3.07	1473 44 / 3.45	1517 46 / 3.83	1561 47 / 4.22								
6900	1541 49 / 3.84	1582 50 / 4.25										

Max Sizeable RPM = 1600 RPM. Table shown extended beyond this point for reference only.

- Motor 00152ET3H182T-W22 has an rpm range of 600 to 1150.
- Motor 00212ET3E184T-W22 has an rpm range of 600 to 1150.
- Motor 00212ET3H184T-W22 has an rpm range of 600 to 1150.
- Motor 00218ET3H145T-W22 has an rpm range of 600 to 1600.
- Motor 00218OT3E56Z-S48PP has an rpm range of 600 to 1600.
- Motor 00318ET3H182T-W22 has an rpm range of 600 to 1600.
- Motor 00318OT3H182T-S has an rpm range of 600 to 1600.
- Motor 00518ET3H184T-W22 has an rpm range of 600 to 1600.
- Motor BMN145-2.0I2-CS-UB1-50 (1200RPM) has an rpm range of 600 to 1200.
- Motor BMN145-2.0I2-CS-UB1-60 (1200RPM) has an rpm range of 600 to 1200.
- Motor BMN145-2.0I2-ES-UB1-50 (1800RPM) has an rpm range of 600 to 1600.
- Motor BMN145-2.0I2-ES-UB1-60 (1800RPM) has an rpm range of 600 to 1600.
- Motor DHP0026 has an rpm range of 600 to 1150.
- Motor DHP0034 has an rpm range of 600 to 1600.
- Motor DTP0014 has an rpm range of 600 to 1600.
- Motor DTP0024 has an rpm range of 600 to 1600.
- Motor DTP0026 has an rpm range of 600 to 1150.
- Motor DTP0034 has an rpm range of 600 to 1600.
- Motor DTP0034-50HZ has an rpm range of 600 to 1438.
- Motor DTP0036 has an rpm range of 600 to 1150.
- Motor DTP0054 has an rpm range of 600 to 1600.
- Motor DTP1/54 has an rpm range of 600 to 1600.
- Motor DTP1/56 has an rpm range of 600 to 1150.
- Motor EP0026 has an rpm range of 600 to 1150.
- Motor GP0024 has an rpm range of 600 to 1600.
- Motor GP0024-50 has an rpm range of 600 to 1440.
- Motor GP0026 has an rpm range of 600 to 1150.
- Motor GP0034 has an rpm range of 600 to 1600.
- Motor GP0034-50 has an rpm range of 600 to 1440.
- Motor GP0054 has an rpm range of 600 to 1600.
- Motor GP1/56 has an rpm range of 600 to 1150.

Motor NP0026 has an rpm range of 600 to 1150.

Motor NP0034 has an rpm range of 600 to 1600.

Motor NP0054 has an rpm range of 600 to 1600.

Performance shown is certified for Installation Type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances in the airstream. The sound ratings shown are loudness values in fan sones at 5 ft (1.5m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for Installation Type A: Free inlet hemispherical sone levels.

FloAire certifies that Model DU200H is licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and 311 and comply with the requirements of the AMCA Certified Ratings Program. Tested to AMCA Standards 210 and 300. Meets California Energy Commission (CEC)

Catalog #110F

May 2024

