

## F2-IBT-200-20Z

CFM	Static Pressure in Inches W.G.												
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1300	585 / 0.07	721 / 0.15	843 / 0.24	955 / 0.34	1059 / 0.44	1156 / 0.55	1245 / 0.66	1327 / 0.77	1410 / 0.90	1486 / 1.02	1557 / 1.15	1625 / 1.28	1693 / 1.42
1700	764 / 0.16	872 / 0.26	971 / 0.37	1064 / 0.48	1153 / 0.61	1238 / 0.73	1320 / 0.87	1397 / 1.00	1471 / 1.14	1543 / 1.28	1611 / 1.43	1677 / 1.58	1740 / 1.73
2100	943 / 0.30	1033 / 0.42	1116 / 0.55	1196 / 0.69	1272 / 0.83	1346 / 0.97	1418 / 1.13	1487 / 1.28	1554 / 1.44	1620 / 1.61	1684 / 1.77	1746 / 1.94	1806 / 2.12
2500	1123 / 0.51	1200 / 0.65	1272 / 0.80	1340 / 0.96	1407 / 1.12	1472 / 1.28	1536 / 1.45	1597 / 1.63	1658 / 1.81	1717 / 1.99	1776 / 2.18	1832 / 2.37	1887 / 2.56
2900	1303 / 0.80	1369 / 0.96	1433 / 1.13	1493 / 1.30	1552 / 1.48	1610 / 1.67	1667 / 1.86	1722 / 2.05	1777 / 2.25	1831 / 2.46	1883 / 2.66	1935 / 2.87	1986 / 3.08
3300	1482 / 1.17	1541 / 1.35	1597 / 1.54	1652 / 1.74	1705 / 1.94	1757 / 2.15	1808 / 2.36	1859 / 2.58	1908 / 2.79	1957 / 3.02	2005 / 3.24	2052 / 3.47	2099 / 3.70
3700	1662 / 1.65	1715 / 1.85	1765 / 2.06	1816 / 2.28	1863 / 2.50	1911 / 2.73	1958 / 2.96	2003 / 3.20	2049 / 3.44	2093 / 3.68	2137 / 3.93	2180 / 4.17	2224 / 4.42
4100	1842 / 2.25	1889 / 2.47	1936 / 2.70	1981 / 2.94	2026 / 3.18	2069 / 3.43	2111 / 3.68	2153 / 3.93	2195 / 4.19	2237 / 4.46	2277 / 4.72		
4500	2022 / 2.97	2065 / 3.22	2108 / 3.47	2149 / 3.73	2190 / 3.99	2230 / 4.26	2269 / 4.53						
4900	2201 / 3.84	2242 / 4.10	2280 / 4.37										

Max Sizeable RPM = 2300 RPM. Table shown extended beyond this point for reference only.

Motor 186735/A01-ECM-50-240-20 has an rpm range of 300 to 2300.

Motor 186735/A01-ECM-60-240-20 has an rpm range of 300 to 2300.

Motor 186741/A01-ECM-50-480-20 has an rpm range of 300 to 2300.

Motor 186741/A01-ECM-60-480-20 has an rpm range of 300 to 2300.