

## F2-IBT-200-22Z

CFM	Static Pressure in Inches W.G.												
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1300	460 / 0.07	608 / 0.16	740 / 0.27	855 / 0.39	957 / 0.52	1050 / 0.66	1136 / 0.81	1216 / 0.96	1291 / 1.11	1361 / 1.27	1429 / 1.43	1493 / 1.60	1553 / 1.77
1700	601 / 0.15	716 / 0.26	827 / 0.39	928 / 0.53	1020 / 0.68	1107 / 0.85	1187 / 1.02	1263 / 1.20	1335 / 1.38	1404 / 1.56	1469 / 1.75	1532 / 1.95	1592 / 2.14
2100	742 / 0.29	835 / 0.42	928 / 0.57	1017 / 0.73	1100 / 0.90	1178 / 1.08	1253 / 1.27	1324 / 1.47	1392 / 1.68	1456 / 1.89	1520 / 2.11	1579 / 2.32	1637 / 2.55
2500	883 / 0.49	961 / 0.65	1040 / 0.81	1118 / 0.99	1192 / 1.17	1263 / 1.37	1332 / 1.58	1397 / 1.80	1461 / 2.03	1522 / 2.26	1580 / 2.50	1633 / 2.72	1694 / 3.00
2900	1025 / 0.77	1091 / 0.95	1160 / 1.13	1228 / 1.33	1294 / 1.53	1359 / 1.75	1422 / 1.98	1482 / 2.21	1541 / 2.45	1598 / 2.71	1653 / 2.96	1707 / 3.23	1760 / 3.50
3300	1166 / 1.13	1224 / 1.33	1284 / 1.54	1344 / 1.76	1404 / 1.98	1462 / 2.21	1519 / 2.46	1575 / 2.71	1630 / 2.97	1683 / 3.24	1735 / 3.52	1786 / 3.80	1835 / 4.09
3700	1307 / 1.59	1359 / 1.82	1412 / 2.05	1466 / 2.29	1520 / 2.53	1572 / 2.78	1625 / 3.05	1676 / 3.31	1727 / 3.59	1776 / 3.88	1824 / 4.17		
4100	1448 / 2.16	1495 / 2.41	1543 / 2.67	1592 / 2.93	1640 / 3.20	1688 / 3.47	1736 / 3.75	1783 / 4.04	1830 / 4.33				
4500	1590 / 2.86	1632 / 3.14	1676 / 3.42	1720 / 3.70	1764 / 3.99	1808 / 4.28	1852 / 4.58						
4900	1731 / 3.69	1770 / 3.99	1809 / 4.29	1850 / 4.60									

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 300 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 300 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 300 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 300 to 1870.