

FAWP-10

CFM	Static Pressure in Inches W.G.				
	0.000	0.125	0.250	0.375	0.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
100		826 / 0.01	1124 / 0.02	1351 / 0.04	1538 / 0.06
200		913 / 0.01	1212 / 0.03	1449 / 0.05	1653 / 0.07
300		1045 / 0.01	1310 / 0.03	1538 / 0.05	1734 / 0.08
400		1194 / 0.02	1444 / 0.04	1646 / 0.06	
500	864 / 0.01	1348 / 0.02	1592 / 0.04	1786 / 0.07	
600	1034 / 0.01	1493 / 0.03	1744 / 0.05		
700	1207 / 0.01	1628 / 0.04			
800	1379 / 0.02	1754 / 0.05			
900	1552 / 0.03				
1000	1724 / 0.04				

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.

Motor BMN42-12011-50-115 has an rpm range of 300 to 1800.

Motor BMN42-12011-60-115 has an rpm range of 300 to 1800.

Motor BMN42-12012-50-230/277 has an rpm range of 300 to 1800.

Motor BMN42-12012-60-230/277 has an rpm range of 300 to 1800.

Motor S33C452VC-01-50-115 has an rpm range of 800 to 1400.

Motor S33C452VC-01-50-230 has an rpm range of 800 to 1400.

Motor S33C452VC-01-60-115 has an rpm range of 800 to 1650.

Motor S33C452VC-01-60-230 has an rpm range of 800 to 1650.