

FAWP-12

CFM	Static Pressure in Inches W.G.								
	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875	1.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
200		707 / 0.01	943 / 0.04	1124 / 0.07	1274 / 0.10	1408 / 0.13	1527 / 0.17	1639 / 0.22	1724 / 0.25
400		860 / 0.02	1090 / 0.05	1266 / 0.08	1413 / 0.11	1550 / 0.16	1667 / 0.20	1778 / 0.24	
600		1010 / 0.03	1242 / 0.06	1418 / 0.10	1567 / 0.14	1695 / 0.18			
800	793 / 0.01	1153 / 0.03	1394 / 0.07	1572 / 0.11	1720 / 0.16				
1000	989 / 0.01	1290 / 0.04	1538 / 0.09	1721 / 0.13					
1200	1187 / 0.02	1432 / 0.06	1678 / 0.10						
1400	1383 / 0.03	1584 / 0.07							
1600	1581 / 0.05	1749 / 0.09							
1800	1779 / 0.07								

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.

Motor BMN42-180I1-50-115 has an rpm range of 300 to 1800.

Motor BMN42-180I1-60-115 has an rpm range of 300 to 1800.

Motor BMN42-180I2-50-230/277 has an rpm range of 300 to 1800.

Motor BMN42-180I2-60-230/277 has an rpm range of 300 to 1800.

Motor CK42BS04M01-50-115 has an rpm range of 1100 to 1400.

Motor CK42BS04M01-50-230 has an rpm range of 1100 to 1400.

Motor CK42BS04M01-60-115 has an rpm range of 1125 to 1620.

Motor CK42BS04M01-60-230 has an rpm range of 1125 to 1620.