

FAWP-14

CFM	Static Pressure in Inches W.G.						
	0.000	0.125	0.250	0.375	0.500	0.625	0.750
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
300		612 / 0.02	836 / 0.06	1007 / 0.11	1149 / 0.16	1277 / 0.22	1389 / 0.29
600		716 / 0.03	916 / 0.07	1081 / 0.12	1224 / 0.18	1351 / 0.24	1467 / 0.31
900	539 / 0.01	856 / 0.04	1034 / 0.09	1183 / 0.14	1314 / 0.20	1433 / 0.27	
1200	716 / 0.02	1007 / 0.06	1174 / 0.11	1310 / 0.17	1432 / 0.23	1542 / 0.31	
1500	893 / 0.03	1162 / 0.08	1324 / 0.14	1451 / 0.20	1566 / 0.27		
1800	1071 / 0.05	1318 / 0.11	1477 / 0.17	1603 / 0.24	1711 / 0.32		
2100	1249 / 0.08	1475 / 0.15	1632 / 0.22	1756 / 0.29			
2400	1427 / 0.12	1634 / 0.20	1788 / 0.28				
2700	1605 / 0.17	1794 / 0.26					
3000	1784 / 0.24						

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.

Motor BMN48-250I1-50-115 has an rpm range of 300 to 1800.

Motor BMN48-250I1-60-115 has an rpm range of 300 to 1800.

Motor BMN48-250I2-50-230/277 has an rpm range of 300 to 1800.

Motor BMN48-250I2-60-230/277 has an rpm range of 300 to 1800.

Motor CK48HF25JF01-50-115 has an rpm range of 1200 to 1350.

Motor CK48HF25JF01-50-230 has an rpm range of 1200 to 1350.

Motor CK48HF25JF01-60-115 has an rpm range of 1200 to 1625.

Motor CK48HF25JF01-60-230 has an rpm range of 1200 to 1625.