

## FAWP-20

CFM	Static Pressure in Inches W.G.										
	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.125	1.250
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
200		415 / 0.03	575 / 0.08	699 / 0.14							
700		513 / 0.04	665 / 0.10	783 / 0.17	883 / 0.25	971 / 0.34	1051 / 0.43	1125 / 0.54	1197 / 0.65	1261 / 0.77	1323 / 0.89
1200	338 / 0.01	605 / 0.06	767 / 0.13	886 / 0.21	984 / 0.30	1071 / 0.40	1151 / 0.51	1223 / 0.63	1289 / 0.74	1354 / 0.88	
1700	478 / 0.02	679 / 0.08	857 / 0.17	983 / 0.26	1086 / 0.37	1174 / 0.48	1254 / 0.60	1326 / 0.73	1393 / 0.86	1457 / 1.00	
2200	617 / 0.04	759 / 0.10	932 / 0.20	1068 / 0.32	1177 / 0.44	1270 / 0.57	1352 / 0.71	1427 / 0.85	1494 / 0.99		
2700	758 / 0.08	862 / 0.14	1004 / 0.24	1142 / 0.37	1258 / 0.51	1357 / 0.66	1443 / 0.81	1520 / 0.97			
3200	898 / 0.13	980 / 0.20	1090 / 0.30	1214 / 0.43	1331 / 0.58	1434 / 0.75	1525 / 0.92				
3700	1038 / 0.20	1106 / 0.27	1193 / 0.37	1295 / 0.50	1403 / 0.66	1505 / 0.84					
4200	1176 / 0.29	1236 / 0.37	1307 / 0.47	1391 / 0.60	1483 / 0.76	1578 / 0.94					
4700	1318 / 0.41	1369 / 0.50	1429 / 0.60	1498 / 0.73	1576 / 0.88						
5200	1458 / 0.55	1504 / 0.65	1556 / 0.76	1615 / 0.89							
5700	1598 / 0.73	1639 / 0.83	1686 / 0.95								
6200	1738 / 0.94										

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.

Motor BMN48-56011-50-115 has an rpm range of 300 to 1800.

Motor BMN48-56011-60-115 has an rpm range of 300 to 1800.

Motor BMN48-56012-50-230/277 has an rpm range of 300 to 1800.

Motor BMN48-56012-60-230/277 has an rpm range of 300 to 1800.

Motor BMN48-75011-E-50-115 has an rpm range of 300 to 1800.

Motor BMN48-75011-E-60-115 has an rpm range of 300 to 1800.

Motor BMN48-75012-E-50-230/277 has an rpm range of 300 to 1800.

Motor BMN48-75012-E-60-230/277 has an rpm range of 300 to 1800.