

FAWPD-36-S

CFM	Static Pressure in Inches W.G.							
	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3500		366 / 0.17	465 / 0.37	539 / 0.60	600 / 0.85	652 / 1.13	700 / 1.44	743 / 1.75
5500	317 / 0.07	438 / 0.26	536 / 0.51	614 / 0.80	678 / 1.11	734 / 1.44	784 / 1.79	829 / 2.16
7500	432 / 0.19	523 / 0.42	608 / 0.71	683 / 1.05	749 / 1.41	806 / 1.80	858 / 2.20	
9500	546 / 0.38	619 / 0.66	690 / 0.99	757 / 1.37	819 / 1.78	876 / 2.21		
11500	661 / 0.68	722 / 1.00	781 / 1.37	840 / 1.78	895 / 2.23			
13500	776 / 1.09	828 / 1.46	879 / 1.88					
15500	891 / 1.66							

Max Sizeable RPM = 900 RPM. Table shown extended beyond this point for reference only.

Motor 00312ET3H213T-W22 has an rpm range of 300 to 900.

Motor 00518ET3H184T-W22 has an rpm range of 438 to 900.

Motor 00518OT3H184T-S has an rpm range of 440 to 900.

Motor DTP0036 has an rpm range of 300 to 900.

Motor DTP0036-50 has an rpm range of 300 to 900.

Motor DTP0054 has an rpm range of 438 to 900.

Motor DTP0054-50 has an rpm range of 358 to 900.

Motor GP0036 has an rpm range of 300 to 900.

Motor GP0036-50 has an rpm range of 300 to 900.

Motor GP0054 has an rpm range of 450 to 900.

Motor GP0054-50 has an rpm range of 360 to 900.