

FAWPD-42-A

CFM	Static Pressure in Inches W.G.						
	0.000	0.250	0.500	0.750	1.000	1.250	1.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3000		503 / 0.39	685 / 1.02	824 / 1.80	940 / 2.70	1043 / 3.70	1135 / 4.80
7000		571 / 0.55	760 / 1.32	905 / 2.25	1025 / 3.30	1130 / 4.45	
11000	428 / 0.21	652 / 0.83	826 / 1.68	970 / 2.73	1093 / 3.91		
15000	583 / 0.53	761 / 1.30	908 / 2.24	1040 / 3.37	1158 / 4.64		
19000	737 / 1.08	887 / 2.02	1012 / 3.08	1128 / 4.29			
23000	893 / 1.92	1022 / 3.05	1131 / 4.24				
27000	1048 / 3.11	1161 / 4.43					

Max Sizeable RPM = 1200 RPM. Table shown extended beyond this point for reference only.

Motor 00512ET3H215T-W22 has an rpm range of 400 to 1150.

Motor 00512OT3H215T-S has an rpm range of 400 to 1150.

Motor DTP0056 has an rpm range of 400 to 1150.

Motor DTP0056-50 has an rpm range of 400 to 958.

Motor GP0056 has an rpm range of 400 to 1150.

Motor GP0056-50 has an rpm range of 400 to 958.