

SA20Z

CFM	Static Pressure in Inches W.G.													
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2000	758 / 0.13	859 / 0.22	955 / 0.33	1046 / 0.45	1131 / 0.58	1213 / 0.71	1291 / 0.85	1365 / 1.00	1437 / 1.15	1507 / 1.30	1574 / 1.46	1638 / 1.62	1701 / 1.78	1762 / 1.95
2500	947 / 0.26	1028 / 0.36	1108 / 0.49	1184 / 0.63	1258 / 0.77	1329 / 0.93	1397 / 1.09	1464 / 1.26	1528 / 1.43	1590 / 1.60	1651 / 1.78	1710 / 1.96	1768 / 2.15	1825 / 2.34
3000	1137 / 0.44	1137 / 0.44	1271 / 0.71	1337 / 0.86	1401 / 1.03	1463 / 1.20	1517 / 1.36	1583 / 1.57	1641 / 1.76	1697 / 1.95	1752 / 2.16	1806 / 2.36	1859 / 2.56	1911 / 2.78
3500	1326 / 0.70	1383 / 0.84	1442 / 1.00	1499 / 1.17	1556 / 1.35	1611 / 1.54	1665 / 1.74	1718 / 1.95	1769 / 2.16	1821 / 2.38	1871 / 2.59	1920 / 2.82	1969 / 3.05	2016 / 3.28
4000	1516 / 1.05	1565 / 1.20	1616 / 1.38	1667 / 1.56	1717 / 1.76	1767 / 1.97	1815 / 2.18	1863 / 2.41	1910 / 2.64	1957 / 2.87	2002 / 3.11	2047 / 3.36	2092 / 3.61	2136 / 3.86
4500	1705 / 1.50	1748 / 1.66	1794 / 1.85	1840 / 2.06	1884 / 2.27	1929 / 2.49	1973 / 2.73	2017 / 2.97	2059 / 3.21	2102 / 3.47	2144 / 3.72	2186 / 3.99	2226 / 4.25	2266 / 4.52
5000	1895 / 2.05	1933 / 2.23	1974 / 2.44	2015 / 2.66	2056 / 2.89	2096 / 3.13	2137 / 3.38	2177 / 3.64	2215 / 3.90	2254 / 4.17	2294 / 4.45			
5500	2084 / 2.73	2119 / 2.93	2156 / 3.15	2193 / 3.39	2230 / 3.63	2267 / 3.89								
6000	2274 / 3.55													

Max Sizeable RPM = 2300 RPM. Table shown extended beyond this point for reference only.

Motor 186735/A01-ECM-50-240-20 has an rpm range of 300 to 2300.

Motor 186735/A01-ECM-60-240-20 has an rpm range of 300 to 2300.

Motor 186741/A01-ECM-50-480-20 has an rpm range of 300 to 2300.

Motor 186741/A01-ECM-60-480-20 has an rpm range of 300 to 2300.